



FASTCAM MH6

2-Megapixel CMOS Image Sensor:

1920 x 1400 pixels at 750fps
 1920 x 1080 pixels at 1,000fps
 1280 x 800 pixels at 2,000fps
 1280 x 256 pixels at 5,000fps

Class Leading Light Sensitivity:

ISO 5,000 color
 ISO 12,500 monochrome

Global Electronic Shutter:

4 μ s independent of frame rate

Dynamic Range (ADC):

24-bit color
 8-bit monochrome

Ultra-Compact and Lightweight:

Camera Heads:

35mm x 35.4mm x 35.4mm, weight 100g
 (0.22 lbs.)

Processor:

210mm x 70mm x 150mm, weight 3kg (6.61 lbs.)

Internal Recording Memory:

24GB divided equally between up to 6 camera heads

High-Speed Interface:

Provides camera control and image download to network via fast Gigabit Ethernet, and USB3 interface for local image download

Memory Backup to Internal SSD:

Automated download to non-volatile 512GB built-in SSD

High-G Rated:

Camera Heads: 160G, 10 msec, 6 axes, 1,000 times

Processor: 100G, 10 msec, 6 axes, 1,000 times

Built-in Acceleration Sensor:

Threshold values can be set to provide record trigger input

Ruggedized multi-head high-speed camera system

Perfectly suited for severely space- and weight-constrained locations commonly found in both on-board vehicle safety testing and military testing applications, the FASTCAM MH6 camera system provides an extraordinary mix of resolution, frame rate, light sensitivity and durability through the incorporation of multiple small and lightweight camera heads with a single processor.

The MH6 allows up to six miniature (35.4mm x 35mm x 35.4mm, 100g) camera heads to be connected to a single processor. Extremely thin and flexible connecting cables are available in varying lengths to accommodate a wide variety of camera head viewing angles and mounting locations. The camera heads are extremely rugged and have been operationally tested to 160G.

Each MH6 camera head provides outstanding image quality with 1080 HD resolution at 1,000 frame per second and an industry leading light sensitivity of ISO 5,000 color and ISO 12,500 monochrome. Camera heads are compatible with readily available 1-inch C-mount ruggedized lenses.

The MH6 system allows automated image download to built-in non-volatile memory. Image transfer to a computer is available via Gigabit Ethernet and USB3.

A built-in 3-axis / 1kHz acceleration sensor can be used to provide a trigger signal to the system if necessary.



Camera Performance Specifications

Model	FASTCAM MH6
Full Frame Performance	750 fps 1920 x 1400 pixels
Example Frame Rates	1,000fps 1920 x 1080 pixels
	2,000fps 1280 x 800 pixels
	5,000fps 1280 x 256 pixels
Minimum Exposure Time	Global electronic shutter to 4µs selectable independent of frame rate
Dynamic Range (ADC)	8-bit monochrome, 24-bit color
Memory Capacity	24GB divided equally between up to 6 connected camera heads with non-volatile memory back-up feature
Sensor Size / Pixel Size	12.672 x 9.24mm (diagonal 15.68mm), 6.6µm square pixel
Input / Output	Input: Trigger (TTL/Switch), sync, ready, event, IRIG Output: trigger, sync, ready, rec, exposure
Camera Control Interface	High-speed Gigabit Ethernet and USB3
Data Storage Media	Built-in 512GB SSD with autosave function
Supported OS	Microsoft Windows operating systems including: 7, 8, 8.1, 10 (32/64-bit)

Mechanical and Environmental Specifications

Mechanical	
Lens Mount	C-mount provided
Camera Head Cable Length	7m or 10m
External Dimensions	
Camera Head (size / weight)	35.4mm (H) x 35mm (W) x 35.4mm (D) / 100 grams (0.22lbs)
Processor (size / weight)	210mm (H) x 70mm (W) x 150mm (D) / 3kg (6.61lbs)
Environmental	
Operating Temperature	0 to 40C, 32° to 104° F
Storage Temperature	-20 to 60C, -4° to 140° F
Humidity	85% or less (non-condensing)
Operational Shock Camera Head	160G, 10ms, 6-axes, 1,000 times
Operational Shock Main Unit	100G, 10ms, 6-axes, 1,000 times

* Specifications subject to change without notice.

PHOTRON USA, INC.
9520 Padgett Street, Suite 110
San Diego, CA 92126
USA

Tel: 858.684.3555 or 800.585.2129
Fax: 858.684.3558
Email: image@photron.com
www.photron.com

PHOTRON EUROPE LIMITED
The Barn, Bottom Road
West Wycombe, Bucks. HP14 4BS
United Kingdom

Tel: +44 (0) 1494 481011
Fax: +44 (0) 1494 487011
Email: image@photron.com
www.photron.com

PHOTRON (Shanghai)
Room 20C, Zhao-Feng
World Trade Building
No. 369, JiangSu Road
ChangNing District
Shanghai, 200050 China
Tel: +86 (0) 21-5268-3700
Email: info@photron.cn
www.photron.cn

PHOTRON LIMITED
Kanda Jinbo-cho 1-105
Chiyoda-ku, Tokyo 101-0051
Japan

Tel: +81 (0) 3 3518-6271
Fax: +81 (0) 3 3518-6279
Email: image@photron.co.jp
www.photron.co.jp



FASTCAM MH6

2-Megapixel CMOS Image Sensor:

1920 x 1400 pixels at 750fps
1920 x 1080 pixels at 1,000fps
1280 x 800 pixels at 2,000fps
1280 x 256 pixels at 5,000fps

Class Leading Light Sensitivity:

ISO 5,000 color
ISO 12,500 monochrome

Global Electronic Shutter:

4µs independent of frame rate

Dynamic Range (ADC):

24-bit color
8-bit monochrome

Ultra-Compact and Lightweight:

Camera Heads:

35mm x 35.4mm x 35.4mm, weight 100g
(0.22 lbs.)

Processor:

210mm x 70mm x 150mm, weight 3kg (6.61 lbs.)

Internal Recording Memory:

24GB divided equally between up to 6 camera heads

High-Speed Interface:

Provides camera control and image download to network via fast Gigabit Ethernet, and USB3 interface for local image download

Memory Backup to Internal SSD:

Automated download to non-volatile 512GB built-in SSD

High-G Rated:

Camera Heads: 160G, 10 msec, 6 axes, 1,000 times

Processor: 100G, 10 msec, 6 axes, 1,000 times

Built-in Acceleration Sensor:

Threshold values can be set to provide record trigger input

Ruggedized multi-head high-speed camera system

Perfectly suited for severely space- and weight-constrained locations commonly found in both on-board vehicle safety testing and military testing applications, the FASTCAM MH6 camera system provides an extraordinary mix of resolution, frame rate, light sensitivity and durability through the incorporation of multiple small and lightweight camera heads with a single processor.

The MH6 allows up to six miniature (35.4mm x 35mm x 35.4mm, 100g) camera heads to be connected to a single processor. Extremely thin and flexible connecting cables are available in varying lengths to accommodate a wide variety of camera head viewing angles and mounting locations. The camera heads are extremely rugged and have been operationally tested to 160G.

Each MH6 camera head provides outstanding image quality with 1080 HD resolution at 1,000 frame per second and an industry leading light sensitivity of ISO 5,000 color and ISO 12,500 monochrome. Camera heads are compatible with readily available 1-inch C-mount ruggedized lenses.

The MH6 system allows automated image download to built-in non-volatile memory. Image transfer to a computer is available via Gigabit Ethernet and USB3.

A built-in 3-axis / 1kHz acceleration sensor can be used to provide a trigger signal to the system if necessary.



Camera Performance Specifications

Model	FASTCAM MH6
Full Frame Performance	750 fps 1920 x 1400 pixels
Example Frame Rates	1,000fps 1920 x 1080 pixels
	2,000fps 1280 x 800 pixels
	5,000fps 1280 x 256 pixels
Minimum Exposure Time	Global electronic shutter to 4µs selectable independent of frame rate
Dynamic Range (ADC)	8-bit monochrome, 24-bit color
Memory Capacity	24GB divided equally between up to 6 connected camera heads with non-volatile memory back-up feature
Sensor Size / Pixel Size	12.672 x 9.24mm (diagonal 15.68mm), 6.6µm square pixel
Input / Output	Input: Trigger (TTL/Switch), sync, ready, event, IRIG Output: trigger, sync, ready, rec, exposure
Camera Control Interface	High-speed Gigabit Ethernet and USB3
Data Storage Media	Built-in 512GB SSD with autosave function
Supported OS	Microsoft Windows operating systems including: 7, 8, 8.1, 10 (32/64-bit)

Mechanical and Environmental Specifications

Mechanical	
Lens Mount	C-mount provided
Camera Head Cable Length	7m or 10m
External Dimensions	
Camera Head (size / weight)	35.4mm (H) x 35mm (W) x 35.4mm (D) / 100 grams (0.22lbs)
Processor (size / weight)	210mm (H) x 70mm (W) x 150mm (D) / 3kg (6.61lbs)
Environmental	
Operating Temperature	0 to 40C, 32° to 104°F
Storage Temperature	-20 to 60C, -4° to 140°F
Humidity	85% or less (non-condensing)
Operational Shock Camera Head	160G, 10ms, 6-axes, 1,000 times

* Specifications subject to change without notice.

TECH IMAGING

Experts in Video Instrumentation

SERVICES, INC.

imaging@techimaging.com

978-740-0063

WWW.TECHIMAGING.COM